



Contents

2001 ANNUAL BOOK OF ASTM STANDARDS, VOLUME 03.04

STANDARDS RELATING TO MAGNETIC PROPERTIES

A complete Subject Index appears at the end of this volume.

Listed below are those standards included in this volume(s) and those standards that have appeared previously which have been discontinued within the past three years.

In the serial designations prefixed to the following titles, the number following the dash indicates the year of original adoption as standard or, in the case of revision, the year of last revision. Thus, standards adopted or revised during the year 2001 have as their final number, 01. A letter following this number indicates more than one revision during that year, that is, 01a indicates the second revision in 2001, 01b, the third revision, etc. Standards that have been reapproved without change are indicated by the year of last reapproval in parentheses as part of the designation number, for example, (2001). A superscript epsilon indicates an editorial change since the last revision or reapproval—^{ε1} for the first change, ^{ε2} for the second change, etc.

*A 34 / A 34M - 96	Practice for Sampling and Procurement Testing of Magnetic Materials
*A 340 - 99a	Terminology of Symbols and Definitions Relating to Magnetic Testing
*A 341 / A 341M - 00	Test Method for Direct Current Magnetic Properties of Materials Using D-C Permeameters and the Ballistic Test Methods
*A 342 / A 342M - 99	Test Methods for Permeability of Feebly Magnetic Materials
*A 343 - 97	Test Method for Alternating-Current Magnetic Properties of Materials at Power Frequencies Using Wattmeter-Ammeter-Voltmeter Method and 25-cm Epstein Test Frame
*A 345 - 98	Specification for Flat-Rolled Electrical Steels for Magnetic Applications
*A 346	Test Method for Alternating-Current Magnetic Performance of Laminated Core Specimens Using the Dieterly Bridge Method (Discontinued 1998†)
*A 348 / A 348M - 00	Test Method for Alternating Current Magnetic Properties of Materials Using the Wattmeter-Ammeter-Voltmeter Method, 100 to 10 000 Hz and 25-cm Epstein Frame
*A 596 / A 596M - 95(1999)	Test Method for Direct-Current Magnetic Properties of Materials Using the Ballistic Method and Ring Specimens
*A 598 - 92(1997)	Test Method for Magnetic Properties Of Magnetic Amplifier Cores
*A 664 - 99	Practice for Identification of Standard Electrical- and Lamination-Steel Grades in ASTM Specifications
*A 677M	Specification for Nonoriented Electrical Steel, Fully Processed Types (Metric) (Discontinued 2000†)
*A 677 / A 677M - 99	Specification for Nonoriented Electrical Steel Fully Processed Types
*A 683M	Specification for Nonoriented Electrical Steel, Semiprocessed Types [Metric] (Discontinued 1999†)
*A 683 / A 683M - 99	Specification for Nonoriented Electrical Steel, Semiprocessed Types
*A 697 - 98	Test Method for Alternating Current Magnetic Properties of Laminated Core Specimen Using Voltmeter-Ammeter-Wattmeter Methods
*A 698 / A 698M - 92(1997) ^{ε1}	Test Method for Magnetic Shield Efficiency in Attenuating Alternating Magnetic Fields
*A 712 - 97	Test Method for Electrical Resistivity of Soft Magnetic Alloys
*A 717 / A 717M - 95	Test Method for Surface Insulation Resistivity of Single-Strip Specimens
*A 719 - 97	Test Method for Lamination Factor of Magnetic Materials
*A 720 - 97	Test Method for Ductility of Nonoriented Electrical Steel
*A 721 - 97	Test Method for Ductility of Oriented Electrical Steel
*A 726 - 00	Specification for Cold-Rolled Magnetic Lamination Quality Steel, Semiprocessed Types
*A 726M	Specification for Cold-Rolled Magnetic Lamination Quality Steel, Semiprocessed Types (Metric) (Discontinued 1998†)
*A 753 - 97	Specification for Wrought Nickel-Iron Soft Magnetic Alloys (UNS K94490, K94840, N14076, N14080)
*A 772 / A 772M - 00	Test Method for ac Magnetic Permeability of Materials Using Sinusoidal Current

^εAdopted by American National Standards Institute.

†Although this standard has been officially withdrawn from Society approval, a brief description is included for information only.

CONTENTS

*A 773 / A 773M - 96	Test Method for dc Magnetic Properties of Materials Using Ring and Permeameter Procedures with dc Electronic Hysteresigraphs
*A 801 / A 801M - 99	Specification for Iron-Cobalt High Magnetic Saturation Alloys
*A 804 / A 804M - 99	Test Methods for Alternating-Current Magnetic Properties of Materials at Power Frequencies Using Sheet-Type Test Specimens
*A 811 - 97	Specification for Soft Magnetic Iron Parts Fabricated by Power Metallurgy Techniques
*A 838 / A 838M - 97	Specification for Free-Machining Ferritic Stainless Soft Magnetic Alloy Bar for Relay Applications
*A 839 / A 839M - 96	Specification for Iron-Phosphorus Powder Metallurgy (P/M) Parts for Soft Magnetic Applications
*A 840M	Specification for Fully Processed Magnetic Lamination Steel (Metric) (Discontinued 2000†)
*A 840 / A 840M - 00	Specification for Fully Processed Magnetic Lamination Steel
*A 848 / A 848M - 96	Specification for Low-Carbon Magnetic Iron
*A 867 / A 867M - 94(1998)*1	Specification for Iron-Silicon Relay Steels
*A 876M	Specification for Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types (Metric) (Discontinued 1998†)
*A 876 / A 876M - 98	Specification for Flat-Rolled, Grain-Oriented, Silicon-Iron, Electrical Steel, Fully Processed Types
*A 883 - 96	Test Method for Ferrimagnetic Resonance Linewidth and Gyromagnetic Ratio of Nonmetallic Magnetic Materials
*A 889 / A 889M - 93(1998)	Test Method for Alternating-Current Magnetic Properties of Materials at Low Inductions Using the Wattmeter-Varmeter-Ammeter-Voltmeter Method and 25-cm [250-mm] Epstein Frame
*A 893 - 97	Test Method for Complex Dielectric Constant of Nonmetallic Magnetic Materials at Microwave Frequencies
*A 894 / A 894M - 00	Test Method for Saturation Magnetization or Induction of Nonmetallic Magnetic Materials
*A 900 - 91(1996)*1	Test Method for Lamination Factor of Amorphous Magnetic Strip
*A 901 - 97	Specification for Amorphous Magnetic Core Alloys, Semi-Processed Types
*A 904 - 98	Specification for 50 Nickel-50 Iron Powder Metallurgy (P/M) Soft Magnetic Parts
*A 912 - 93(1998)	Test Method for Alternating-Current Magnetic Properties of Amorphous Materials at Power Frequencies Using Wattmeter-Ammeter-Voltmeter Method with Toroidal Specimens
*A 927 / A 927M - 99	Test Method for Alternating-Current Magnetic Properties of Toroidal Core Specimens Using the Voltmeter-Ammeter-Wattmeter Method
*A 932 / A 932M - 95	Test Method for Alternating-Current Magnetic Properties of Amorphous Materials at Power Frequencies Using Wattmeter-Ammeter-Voltmeter Method with Sheet Specimens
*A 937 - 95	Test Method for Determining Interlaminar Resistance of Insulating Coatings Using Two Adjacent Test Surfaces
A 971 - 00	Test Method for Measuring Edge Taper and Crown of Flat-Rolled Electrical Steel Coils
*A 976 - 97	Classification of Insulating Coatings by Composition, Relative Insulating Ability and Application
*A 977 - 97	Test Method for Magnetic Properties of High-Coercivity Permanent Magnet Materials Using Hysteresigraphs
A 1009 - 00	Specification for Soft Magnetic MnZn Ferrite Core Materials for High Frequency (10 kHz-1 MHz) Power Transformer and Filter Inductor Applications
A 1013 - 00	Test Method for High-Frequency (10 kHz-1 MHz) Core Loss of Soft Magnetic Core Components at Controlled Temperatures Using the Voltmeter-Ammeter-Wattmeter Method

RELATED MATERIAL

SI Quick Reference Guide	305
Index	309